

COBOS

precision

AUW/AUX/AUY - Series



Standard features.

Innovative UniBloc-Technology.

Different Units like: Milligram, Carat, Grain, Gramme, Mom, Tael...

Temperature and time-controlled internal calibration.

Formulation mode for receipts and prescriptions.

Automatic span calibration;


- Fully-automatic calibration by temperature detection (PSC).
- Fully-automatic calibration at user pre-set times (CLOCK-CAL).
- Span calibration at any time: Touch key calibration.

Piece-counting function.

Windows-Direct-Function.

below-weigh hook for hanging measurement.

Metal housing.

Verifiable models. 

Accessories

Density kit.



Density Kit

Software for specific gravity measurements of solids and liquids pre-installed.

Electronic Dot-Matrix printers EP80/EP90 optional available. GMP/GLP compliant. Can be used together with Windows-Direct-Function.



EP-80 printer



EP-90 printer

Model	PN	Capacity (Max)	Standard deviation	Internal calibration	linearity (mg)	Min. display (d)	Pan size
AUW-120	321-62900-21	120 g	0,1 mg	yes	0,2	0,1 mg	ø 80
AUW-220	321-62900-22	220 g	0,1 mg	yes	0,2	0,1 mg	ø 80
AUW-320	321-62900-24	320 g	0,15 mg	yes	0,3	0,1 mg	ø 80
AUX-120	321-62900-25	120 g	0,1 mg	yes	0,2	0,1 mg	ø 80
AUX-220	321-62900-26	200 g	0,1 mg	yes	0,2	0,1 mg	ø 80
AUX-320	321-62900-27	320 g	0,15 mg	yes	0,3	0,1 mg	ø 80
AUY-120	321-62900-28	120 g	0,1 mg	no	0,2	0,1 mg	ø 80
AUY-220	321-62900-29	220 g	0,1 mg	no	0,2	0,1 mg	ø 80