

COBOS

precision

JT-A Series



0,1mg. Tuning-fork technologies bring new concept for analytical balances.

automatic internal calibration (JT/AI).

ISO/GLP/GMP

Back lit LCD. Measurement result is easily readable with bright display.



Back lit LCD

RS232C interface is equipped to connect to PC, printer and other outside devices.



RS232C interface

Different units like: ct, lb, oz...

Anti-electrostatic 360 degree transparent windshield.



Anti-electrostatic 360 degree transparent windshield.

Full automatic span adjustment, automatic repeatability measurement (ARM). For (JT/AR) type only.

Verifiable models. M

Accessories

Models JT-A include calibration weight.

Density measurement kit.



Density Kit

Statistical printer CSP-160.



Statistical printer CSP-160

Software: RTS-E; interface for windows.

Model	PN	Capacity (Max)	Readability (d)	Calibration	Plato Inox.
JT-A-80	100-10014	80 g	0,0001 g	External	ø 80
JT-A-120	100-10015	120 g	0,0001 g	External	ø 80
JT-A-220	100-10016	220 g	0,0001 g	External	ø 80
JT-AI-80	100-10017	800 g	0,0001 g	Internal	ø 80
JT-AI-120	100-10018	120 g	0,0001 g	Internal	ø 80
JT-AI-220	100-10019	220 g	0,0001 g	Internal	ø 80