

COBOS

precision

410 SRS/SRC Series



Indicators and Bases of great durability, rigidity and structural integrity

Backlit display.

RS-232C standard.

Base in stainless steel (SRC) or frame of aluminium / platform of steel (SRS)

Protection IP-67 (SRC)

Protection IP-65 (SRS)

Other features (depending on terminal).



Base

Bases	PN	Capacity (Max)	Readability (d)	Pan size
SRS 75K	410-9900-001	75 Kg	5 g	400x500
SRS 150K	410-9901-001	150 Kg	10 g	400x500
SRS 300K	410-9902-001	300 Kg	20 g	400x500
SRC 75K	410-9910-001	75 Kg	5 g	380x500
SRC 150K	410-9911-001	150 Kg	10 g	380x500

SRD Indicator

ABS or stainless steel.

Protection IP-67.

Large LC display backlight.

battery operation.

RS-232-C standard.

Selectable weighing unit (Kg/lb).

Check weighing program.



Backlight indicator SRD

SRM Indicator

ABS or stainless steel.

Protection IP-67.

Large LC display backlight.

battery operation.

RS-232-C standard.

Selectable weighing unit (Kg/lb).

Piece counting.

Direct ID and date settings.



Indicator with numerical keyboard SRM (stainless steel)

Indicators	PN
SRD ABS	410-9922-001
ARD stainless steel	410-9923-001
SRM ABS	410-9920-001
SRM stainless steel	410-9921-001

Accessories

Wall-mount for display.

Display with column.

Rechargeable battery (24h aprox de autonomía con trabajo continuado).

Software: BALINT; interface for windows.

Calibration weight.