

COBOS

precision

DK - Series



High resolution with high technology

Anti-theft lock code.

Password protection for stored programs.

Clock with date and time.

You can separate the indicator (cable length 1m.).



Separate type

Logging of the measuring results in conformance with ISO and GLP.

Configurable printing protocol.

Protective cover.

4 directly programmable function keys (freely selectable).

Specifications

Weighing range: 12100g. to 62000g. Dual Range & Floating Range.

Readability: 0,1g. 1g. and dual-range.

Linearity: $\leq \pm 0,5g$.

Reproducibility: $\leq 1g$.

Weighing platform: 400x300mm.

Protection: IP65 optional.

Data port: RS232/V4 bi-directional.

Calibration: SCS Internal Standard.

Display: VFD standard.

Applications: Enhanced + Count or FPVO specialty.

Operating temperature: 0-40°C.

Power consumption: 85-240 VAC 50-60Hz 13 VA.

Accessories

Protection IP-65.

Under weighing hook until 40 Kg.

Under weighing hook. (IP-65 version) until 40 Kg.

Display with column.



Display with column

Extended pick-up cable 1,5 m. to 10 m. (by order).

Dot-matrix printer CBM910.



Dot-matrix printer CBM910

Software: BALINT; interface for windows.

Model	PN	Capacity (Max)	Readability (d)	Calibration	Pan size
D-12DK	490-9528	12.100 g	0,1 g	Internal	400x300
D-18DK	490-9529	18.100 g	0,1 g	Internal	400x300
D-24DK	490-9530	24.100 g	0,1 g	Internal	400x300
D34DK	490-9531	34.100 g	0,1 g	Internal	400x300
G-20DK	490-9606	20.100 g	1 g	Internal	400x300
G-30DK	490-9607	30.100 g	1 g	Internal	400x300
G-40DK	490-9608	40.100 g	1 g	Internal	400x300
G-60DK	490-9609	62.100 g	1 g	Internal	400x300
DR-34DK	490-9805	12.100 g /34.100 g	0,1 / 1 g	Internal	400x300
FR-34DK	490-9532	12.100 g / 34.100 g	0,1 / 1 g	Internal	400x300