

COBOS

precision

POWER SONIC 603



The most powerful Ultrasonic cleaner

Built-in microprocessor controller.

High-performance industrial BLT transducer.

Selectable use of ultrasonic power; (3 steps - Low, Medium, High).

Degassing function.

User-friendly control panel for easy and simple operation.

Elegant style and strong durability.

Lid to see the inside of the bath.

Built-in alarm function for operation stop.

Silicon rubber heater for durability and stability (Option).

Drain valve (Option).

Stainless steel basket (Option).

Applications

- Surgical / Dental instruments
 - Lab glassware
 - Scientific instruments and components
 - Metal parts and assemblies
 - Plastic parts and assemblies
 - PC boards
 - Electrical / Electronic components
 - Jewelry / Watches / Clock movements
 - Optical equipment
 - Eyeglasses / Frames
 - Veterinary instruments
-

Series	POWER SONIC 603
Transducer	BLT industrial
Time range	0-99 min.
Temperature range	0-60°C
Frequency	44 Khz.
Housing material	SUS 304 + ABS
Bath capacity (litros)	3,3
Bath dimensions (mm.)	240x140x100
Overall dimensions (mm.)	325x225x255
Basket dimensions (mm.)	230x135x105
Net weight (Kg)	4,5
Required power	200W
Voltage	AC 110 ~ 240 V 50/60Hz